

ECODUO

DESCRIPTION

The 3.2mm thick Ecoduo® acoustic underlayment membrane is an innovative, environmentally friendly solution made from recycled synthetic fibers. It provides excellent sound insulation for residential projects and multi-story buildings. Thanks to its special composition, it effectively reduces unwanted noise such as footsteps and vibrations, creating a calm and comfortable environment. Additionally, its integrated vapor barrier membrane protects against unwanted moisture, ensuring the durability of the flooring. By choosing Ecoduo®, you are selecting a high-performance product that contributes to environmental preservation, combining acoustic comfort and ecological responsibility.

CHARACTERISTICS

The Ecoduo® acoustic underlayment membrane offers the following characteristics and advantages:

- Fast and easy installation;
- Reduces impact and airborne noises;
- Great protection against humidity and moisture;
- Unscented;
- Non-toxic;
- Amplifies the thermal insulation value of the floor;
- 100 % recycled content;
- Designed with Leed® philosophy in mind;
- Suitable for all types floating floors.



TECHNICAL PROPERTIES

Coverage	100 pi² (9,29 m²) sq. ft.
Length	33,3' (10,25 m)
Width	36" (0,91 m)
Thickness	1/8" (3,2 mm)
Vapor barrier	0,2 mm
FIIC	57
ASTC	66

INSTRUCTIONS FOR USE

- Unroll the material parallel to the wall with the vapor barrier facing up.
- Seal the seams with vapor barrier tape without overlapping the felt.
- Install floor planks perpendicular to the long side of the acoustical felt underlayment.

NEED TO KNOW MORE?

Call your representative for your projects! 1 800 463-8929 | texel.ca

485, rue des Erables, Saint-Elzear (Quebec) G0S 2J1