

Product Information Sheet



FyreWrap® LiB Films

INTRODUCTION

FyreWrap® LiB (Lithium-ion Battery) Films from Alkegen are high-temperature, lightweight flame barriers and electrically insulating materials designed to increase safety and performance in lithium-ion battery packs. Based on proprietary fire blocking technology, the film was developed as a flame barrier for applications demanding extremely lightweight materials.

FYREWRAp LiB FILMS FEATURES

- Fire resistant, flame barrier
- Electrically insulating
- Suitable for temperatures in excess of 1100°C
- Uniform lightweight flexible sheets
- Easy to wrap, shape or cut
- Heat-sealable and adhesive back versions available
- Designed for minimum moisture absorption and reduced installed weight

FILM CAPABILITIES

- Aid in thermal runaway propagation prevention
- Short circuit prevention and electrical protection
- Cascading fire prevention
- Thermal isolation and containment

APPLICATIONS

- Battery Enclosures / Lids
 - Aluminum, Steel, Copper, and other metals
 - Composites
- Busbars, current collectors
- Battery sub-components where high voltage electrical and fire protection are needed
- Packaging



MATERIAL PROPERTIES

- Resistant to temperatures in excess of 1100°C
- Nominal Thickness: 0.12mm
- Permeance: < 0.2 perms
- UL 94 VTM-0 / V-0*
- ASTM E1461 Flash Method Thermal Conductivity: 0.202 (W/m-K)
- Dielectric Strength ASTM D149-09 (2013): 700-800 (volts/mil) / 20 (kV/mm)
- 60 Hz Dielectric Constant ASTM D150-II: 1.97 DC 0.0087 (DF)
- 10 kHz Dielectric Constant ASTM D150-II: 2.08 DC 0.0071 (DF)
- Arc Resistance ASTM D495-14: 14.0
- Volume and Surface Resistivity ASTM D257-14:
 - Volume Resistivity: 5.36e+14 (ohm-cm)
 - Surface Resistivity: 1.07e+11 (ohms/square cm)

*tested in accordance with UL VTM-0 testing or when used in a compatible V-0 composite

Please contact Alkegen for more information on FyreWrap LiB films and coatings along with any specific design requirements.

The following are registered trademarks of Alkegen: FyreWrap.

The test data shown are average results of tests conducted under standard procedures and are subject to variation. Results should not be used for specification purposes. Product Information Sheets are periodically updated by Alkegen. Before relying on any data or other information in this Product Information Sheet, you should confirm that it is still current and has not been superseded. A Product Information Sheet that has been superseded may contain incorrect, obsolete and/or irrelevant data and other information.

Form A-5259
Effective 10/23
© 2023 Alkegen
All Rights Reserved

Alkegen
Headquarters
5215 N. O'Connor Blvd, Suite 2300
Irving, TX 75039
Telephone: 716-768-6500
Website: www.alkegen.com
Email: batterygroup@alkegen.com

