

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : DPF HARD CEMENT
UFI : 3C3A-90RC-M00H-M0FC

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Industrial use
Use of the substance/mixture : For industrial use within high temperature applications.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer/Supplier**

Alkegen (formerly Unifrax)
Mill Lane, Rainford
UK– WA11 8LP St Helens, Merseyside
United Kingdom
T + 44 (0) 1744 88 7600 - F + 44 (0) 1744 88 9916

Distributor

Alkegen (formerly Unifrax)
Kleinreinsdorf 62
DE– 07989 Teichwolframsdorf
Germany
T + 49 (0) 366 24 40020 - F + 49 (0) 366 24 40099

Distributor

Alkegen (formerly Unifrax)
Shaftsbury Street
DE23 8XA Derby
United Kingdom
T +44 (0) 1332 331808

Distributor

Alkegen (formerly Unifrax)
Via Volonterio 19
21047 Saronno (VA)
Italy
T +39 02 967 01 808 - F +39 02 962 5721

Email competent person

reachsds@alkegen.com

Distributor

Alkegen (formerly Unifrax)
17 Rue Antoine Durafour
42420 Lorette
France
T +33 (0) 477 737 032 - F +33 (0) 477 733 991

Distributor

Alkegen (formerly Unifrax)
Ruská 311, Pozorka
CZ– 417 03 Dubí 3
Czech Republic
T + 42 (0) 417 800 356 - F + 42 (0) 417 539 838

Distributor

Alkegen (formerly Unifrax)
Cristobal Bordiu 20
ES– 28003 Madrid
Spain
T + 34 91 395 2279 - F + 34 91 395 2124

1.4. Emergency telephone number

Emergency number : Occupational Hygiene and CARE: Tel: + 44 (0) 1744 887603; Email: reachsds@alkegen.com; (8.15-17.10 h); Language : English

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
AES wool (synthetic fibres, alkaline earth silicate) (436083-99-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Disodium edetic acid (EDTA), dihydrate (6381-92-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
edetic acid (EDTA) (60-00-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
silicon carbide substance with national workplace exposure limit(s) (GB)	CAS-No.: 409-21-2 EC-No.: 206-991-8	$\geq 25 - < 50$	Not classified
AES wool (synthetic fibres, alkaline earth silicate) substance with national workplace exposure limit(s) (GB) (Note A)(Note Q)(Note R)	CAS-No.: 436083-99-7 EC Index-No.: 650-016-00-2 REACH-no: 01-2119457644-32-0001;01-2119457644-32-0002	$\geq 20 - < 25$	Not classified
Disodium edetic acid (EDTA), dihydrate	CAS-No.: 6381-92-6 EC-No.: 205-358-3	$\geq 2.5 - < 5$	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373
edetic acid (EDTA)	CAS-No.: 60-00-4 EC-No.: 200-449-4 EC Index-No.: 607-429-00-8	$\geq 1 - < 2.5$	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Eye Irrit. 2, H319 STOT RE 2, H373

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Note A : Without prejudice to Article 17(2), the name of the substance must appear on the label in the form of one of the designations given in Part 3. In Part 3, use is sometimes made of a general description such as '... compounds' or '... salts'. In this case, the supplier is required to state on the label the correct name, due account being taken of section 1.1.1.4.

Note Q : The harmonised classification as a carcinogen applies unless one of the following conditions is fulfilled: — a short term biopersistence test by inhalation has shown that fibres longer than 20 µm have a weighted half-life less than 10 days; or — a short term biopersistence test by intratracheal instillation has shown that the fibres longer than 20 µm have a weighted half-life less than 40 days; or — an appropriate intra-peritoneal test has provided no evidence of excess carcinogenicity; or — no relevant pathogenicity or neoplastic changes are noted in a suitable long term inhalation test

Note R : The harmonised classification as a carcinogen applies except in the case of fibres with a Length Weighted Geometric Mean Diameter (LWGMD) minus two geometric standard errors greater than 6 µm, as measured in accordance with Test method A.22 in the Annex to Commission Regulation (EC) No 440/2008 (1).

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. The product is not flammable. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.
--	---

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes.
------------------	-------------------------------------

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from : Acids, Heat sources. Store in a well-ventilated place. Keep cool.

Incompatible materials : Non ferrous metals (Al, Cu, Zn) and their alloys.

Storage temperature : 5 – 20 °C

Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

Packaging materials : Original packaging.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

AES wool (synthetic fibres, alkaline earth silicate) (436083-99-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Man made vitreous fibers (MMVF)
Remark	The NOEL of 30 x 10 ⁶ WHO-f/m ³ or 10 x 10 ⁶ f with l > 20 µm is used as the starting point to derive an OEL. Taking into account this well defined NOEL, a LOEL at fivefold higher concentrations, and the absence of a carcinogenic potential in long term inhalation studies allows to apply the small uncertainty factor of 3 resulting in the OEL of 10 f/ml (10x10 ⁶ fibres /m ³ or 1 mg/m ³). (Year of adoption 2002)
Regulatory reference	SCOEL Recommendations
United Kingdom - Occupational Exposure Limits	
Local name	MMMF (Machine-made mineral fibre)
WEL TWA (OEL TWA) [1]	5 mg/m ³ (except for refractory ceramic fibres and special purpose fibres)
WEL TWA (OEL TWA) [2]	2 fibers/ml (except for refractory ceramic fibres and special purpose fibres)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
silicon carbide (409-21-2)	
United Kingdom - Occupational Exposure Limits	
Local name	Silicon carbide

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

WEL TWA (OEL TWA) [1]	10 mg/m ³ (not whiskers), total inhalable 4 mg/m ³ (not whiskers), respirable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

edetic acid (EDTA) (60-00-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	3 mg/m ³
Acute - local effects, inhalation	3 mg/m ³
Long-term - systemic effects, inhalation	1.5 mg/m ³
Long-term - local effects, inhalation	1.5 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	1.2 mg/m ³
Long-term - systemic effects, oral	25 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.6 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	2.17 mg/l
PNEC aqua (marine water)	0.217 mg/l
PNEC (Soil)	
PNEC soil	1.11 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	50 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Use splash goggles when eye contact due to splashing is possible. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN ISO 13688. EN 13034

Hand protection:

In case of repeated or prolonged contact wear gloves. Nitrile rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

Liquid product : Inhalation unlikely. Dust production: dust mask with filter type P2. EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use. Do not take working clothes home. Separate working clothes from town clothes. Launder separately.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Viscous.
Odour	: odourless.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water: Slightly soluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1090 kg/m ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

DPF HARD CEMENT	
ATE CLP (dust,mist)	> 5 mg/l/4h

Disodium edetic acid (EDTA), dihydrate (6381-92-6)

LC50 Inhalation - Rat (Dust/Mist)	> 1000 mg/m ³ (6 h; (OECD 412 method))
-----------------------------------	---

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

edetic acid (EDTA) (60-00-4)

NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight/day (male; Read-across)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	3 mg/m ³ (Read-across; (OECD 413 method))
STOT-repeated exposure	May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).

Disodium edetic acid (EDTA), dihydrate (6381-92-6)

LOAEC (inhalation, rat,dust/mist/fume, 90 days)	≈ 30 mg/m ³ (male; (OECD 412 method))
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (if inhaled).

Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
-------------------	---

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Other information

: Irritant Properties

When tested using approved methods (Directive 67/548/EC, Annex V, Method B4), fibres contained in this material give negative results. All man made mineral fibres, like some natural fibres, can produce a mild irritation resulting in itching or rarely, in some sensitive individuals, in slight reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by a temporary mechanical effect. Other Animal Studies

These materials have been designed to allow rapid clearance from tissue. And this low biopersistence has been confirmed in many studies using EU protocol ECB/TM/27(rev 7) and the German method specified in TRGS 905 (1999). When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Not rapidly degradable

12.2. Persistence and degradability

AES wool (synthetic fibres, alkaline earth silicate) (436083-99-7)	
Persistence and degradability	Not applicable.
edetic acid (EDTA) (60-00-4)	
Persistence and degradability	Not readily biodegradable.
Disodium edetic acid (EDTA), dihydrate (6381-92-6)	
Persistence and degradability	EDTA and salts thereof : Not readily biodegradable.

12.3. Bioaccumulative potential

AES wool (synthetic fibres, alkaline earth silicate) (436083-99-7)	
Partition coefficient n-octanol/water (Log Kow)	Not applicable
Bioaccumulative potential	Not applicable.
edetic acid (EDTA) (60-00-4)	
Partition coefficient n-octanol/water (Log Pow)	-3.86 (25 °C)
Disodium edetic acid (EDTA), dihydrate (6381-92-6)	
Partition coefficient n-octanol/water (Log Pow)	-11.7
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

AES wool (synthetic fibres, alkaline earth silicate) (436083-99-7)	
Ecology - soil	Not applicable.
Disodium edetic acid (EDTA), dihydrate (6381-92-6)	
Ecology - soil	Not relevant.

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

DPF HARD CEMENT

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.

Product/Packaging disposal recommendations : Recycle or dispose of in compliance with current legislation.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

DPF HARD CEMENT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Data sources : European Chemicals Agency, <http://echa.europa.eu/>. Information provided by the manufacturer.

Other information : Occupational Hygiene: dawn.webster@alkegen.com.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
EUH210	Safety data sheet available on request.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

KFT SDS EU 06

The information presented on this SDS (1) provides details on material identity, manufacturer/supplier information, hazard characterization and prevention, emergency response and other specialized information, (2) is considered to be accurate to the best of our knowledge, information and good faith belief as of the date of publication, (3) is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release of the material named, (4) should be read and used in conjunction with the company's relevant literature, (5) relates only to the specific material designated and may not be valid for such material used in combination with any other material or process and (6) is provided without warranty, expressed or implied, in law or in fact, of merchantability or fitness for a particular purpose. This document does not constitute a product specification and should not be relied on as such. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product.