

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : FIXWOOL RIGIDIZER D20
UFI : P66A-00HF-Q00U-F8PG
Product code : 1041

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : For industrial use within high temperature applications.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Alkegen (formerly Unifrax)
Mill Lane, Rainford
UK- WA11 8LP St Helens, Merseyside
United Kingdom
T + 44 (0) 1744 88 7600 - F + 44 (0) 1744 88 9916

Email competent person

reachsds@alkegen.com

Distributor

Alkegen (formerly Unifrax)
Kleinreinsdorf 62
DE- 07989 Teichwolframsdorf
Germany
T + 49 (0) 366 24 40020 - F + 49 (0) 366 24 40099

Distributor

Alkegen (formerly Unifrax)
17 Rue Antoine Durafour
42420 Lorette
France
T +33 (0) 477 737 032 - F +33 (0) 477 733 991

Distributor

Alkegen (formerly Unifrax)
Shaftsbury Street
DE23 8XA Derby
United Kingdom
T +44 (0) 1332 331808

Distributor

Alkegen (formerly Unifrax)
Ruská 311, Pozorka
CZ- 417 03 Dubí 3
Czech Republic
T + 42 (0) 417 800 356 - F + 42 (0) 417 539 838

Distributor

Alkegen (formerly Unifrax)
Via Volonterio 19
21047 Saronno (VA)
Italy
T +39 02 967 01 808 - F +39 02 962 5721

Distributor

Alkegen (formerly Unifrax)
Cristobal Bordiu 20
ES- 28003 Madrid
Spain
T + 34 91 395 2279 - F + 34 91 395 2124

1.4. Emergency telephone number

Emergency number : Occupational Hygiene and CARE: Tel: + 44 (0) 1744 887603; Email: reachsds@alkegen.com; (8.15-17.10 h); Language : English

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning
Contains : 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one
Hazard statements (CLP) : H317 - May cause an allergic skin reaction.
Precautionary statements (CLP) : P261 - Avoid breathing dust, mist, spray.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
ethanediol (107-21-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methyl-2H-isothiazol-3-one (2682-20-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Mixture of the substances listed below with non-hazardous additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanediol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	$\geq 5 - < 10$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=670 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	< 0.1	Acute Tox. 2 (Inhalation), H330 (ATE=0.1 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=242 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=120 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
------------------------------	--	-------	--

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	(0.05 ≤C < 100) Skin Sens. 1, H317
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Allergic reactions.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: The product is not flammable. Use extinguishing media appropriate for surrounding fire. Foam. Dry powder. Carbon dioxide. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide. Aldehydes.

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Concerning personal protective equipment to use, see section 8.
Emergency procedures : Prohibit unauthorized persons.

6.1.2. For emergency responders

Protective equipment : Ensure adequate ventilation. Concerning personal protective equipment to use, see section 8.
Emergency procedures : Manipulations are to be done only by qualified and authorised persons.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.
High efficiency particulate air filter (HEPA filter).

6.4. Reference to other sections

See section 7. See Section 8. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with skin and eyes. Avoid inhalation of vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Product must only be kept in the original packaging. Keep container closed when not in use.
Protect against frost.
Storage temperature : 5 – 20 °C
Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethanediol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IOEL TWA	52 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	104 mg/m ³
IOEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m ³ particulate 52 mg/m ³ vapour
WEL TWA (OEL TWA) [2]	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m ³ vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

ethanediol (107-21-1)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	106 mg/kg bodyweight/day
Long-term - local effects, inhalation	35 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, dermal	53 mg/kg bodyweight/day
Long-term - local effects, inhalation	7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC aqua (intermittent, freshwater)	10 mg/l
PNEC aqua (intermittent, marine water)	10 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	37 mg/kg dwt
PNEC sediment (marine water)	3.7 mg/kg dwt
PNEC (Soil)	
PNEC soil	1.53 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	199.5 mg/l

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6.81 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1.2 mg/m ³
Long-term - systemic effects, dermal	0.345 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4.03 µg/L
PNEC aqua (marine water)	0.403 µg/L
PNEC aqua (intermittent, freshwater)	1.1 µg/L
PNEC aqua (intermittent, marine water)	0.11 µg/L
PNEC (Sediment)	
PNEC sediment (freshwater)	49.9 µg/kg dw
PNEC sediment (marine water)	4.99 µg/kg dw
PNEC (Soil)	
PNEC soil	3 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1.03 mg/l
2-methyl-2H-isothiazol-3-one (2682-20-4)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.043 mg/m ³
Long-term - local effects, inhalation	0.021 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.053 mg/kg bodyweight/day
Acute - local effects, inhalation	0.043 mg/m ³
Long-term - systemic effects, oral	0.027 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.021 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	3.39 µg/L
PNEC aqua (marine water)	3.39 µg/L
PNEC aqua (intermittent, freshwater)	3.39 µg/L
PNEC aqua (intermittent, marine water)	3.39 µg/L
PNEC (Soil)	
PNEC soil	0.047 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.23 mg/l

8.1.5. Control banding

No additional information available

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses with side shields. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Impervious clothing. Do not take working clothes home

8.2.2.3. Respiratory protection

Respiratory protection:

Liquid product : Inhalation unlikely. If dust are formed : Wear appropriate mask, Particle filter, P2. EN 149.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Appearance	: Paste.
Odour	: odourless.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 10 – 10.5
Viscosity, kinematic	: Not available
Solubility	: Water: Soluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No additional information available.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

FIXWOOL RIGIDIZER D20	
ATE CLP (oral)	> 7000 mg/kg bodyweight
ethanediol	
LD50 oral	≈ 1600 mg/kg bodyweight (human (estimated value))
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	670 – 784 mg/kg bodyweight (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
2-methyl-2H-isothiazol-3-one (2682-20-4)	
LD50 oral rat	120 mg/kg bodyweight (EPA OPPTS 870.1100)
LD50 dermal rat	242 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat (Dust/Mist)	0.1 mg/l/4h (OECD 403 method)

Skin corrosion/irritation : Not classified
pH: 10 – 10.5
Serious eye damage/irritation : Not classified
pH: 10 – 10.5
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

2-methyl-2H-isothiazol-3-one (2682-20-4)	
NOAEL (chronic, oral, animal/male, 2 years)	> 400 ppm (mouse)

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

STOT-repeated exposure : Not classified

ethanediol	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	2.18 mg/l (96 h; Onchorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	2.94 mg/l (48 h; Daphnia magna; OECD 202)
ErC50 algae	0.15 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)
NOEC chronic algae	0.055 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)

2-methyl-2H-isothiazol-3-one (2682-20-4)	
LC50 - Fish [1]	4.77 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))
EC50 - Crustacea [1]	0.934 mg/l (48 h; Daphnia magna; (OECD 202 method))
EC50 72h algae	0.103 mg/l (72 h, Pseudokirchneriella Subcapita; (OECD 201 method))
ErC50 algae	0.072 mg/l (OECD 201 method)
NOEC chronic fish	4.93 mg/l (98 d; Oncorhynchus mykiss; (OECD 210 method))
NOEC chronic crustacea	0.044 mg/l (21 d; Daphnia magna; (OECD 211 method))
NOEC chronic algae	0.05 mg/l (5 d; Pseudokirchneriella subcapitata; (OECD 201 method))

12.2. Persistence and degradability

ethanediol	
Biodegradation	90 – 100 % (10 d; (OECD 301A method))

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	85 % (63 d; (OECD 301C method))

2-methyl-2H-isothiazol-3-one (2682-20-4)	
Persistence and degradability	Not readily biodegradable. (OECD 301B method). (OECD 301D method).

12.3. Bioaccumulative potential

ethanediol	
Partition coefficient n-octanol/water (Log Pow)	-1.36 (Quantitative structure-activity relationship (QSAR))

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
BCF - Fish [1]	6.95 (OECD 305 method)
Partition coefficient n-octanol/water (Log Kow)	0.7 (20 °C; pH 7; Test method EU A.8)
2-methyl-2H-isothiazol-3-one (2682-20-4)	
Partition coefficient n-octanol/water (Log Pow)	-0.486 (20 °C)
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

2-methyl-2H-isothiazol-3-one (2682-20-4)	
Surface tension	68.8 mN/m (19 °C, EEC Method A5)
Ecology - soil	Low mobility (soil).

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code : 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Transport regulations (ADR) : Not applicable

Transport by sea

Transport regulations (IMDG) : Not applicable

Air transport

Transport regulations (IATA) : Not applicable

Inland waterway transport

Transport regulations (ADN) : Not applicable

Rail transport

Transport regulations (RID) : Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	FIXWOOL RIGIDIZER D20 ; ethanediol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Data sources

: European Chemicals Agency, <http://echa.europa.eu/>. MSDSs of the suppliers.

Other information

: Occupational Hygiene: dawn.webster@alkegen.com. Please refer to specific technical data sheet for more information.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

FIXWOOL RIGIDIZER D20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Sens. 1	H317	Calculation method
--------------	------	--------------------

KFT SDS EU 06

The information presented on this SDS (1) provides details on material identity, manufacturer/supplier information, hazard characterization and prevention, emergency response and other specialized information, (2) is considered to be accurate to the best of our knowledge, information and good faith belief as of the date of publication, (3) is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release of the material named, (4) should be read and used in conjunction with the company's relevant literature, (5) relates only to the specific material designated and may not be valid for such material used in combination with any other material or process and (6) is provided without warranty, expressed or implied, in law or in fact, of merchantability or fitness for a particular purpose. This document does not constitute a product specification and should not be relied on as such. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product.