

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : FyreWrap® LiB G2 Coating  
UFI : QDA5-E15R-5001-WUVA

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Industrial use  
Use of the substance/mixture : For industrial use within high temperature applications.

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Supplier**

Alkegen (formerly Unifrax)  
Mill Lane, Rainford  
UK- WA11 8LP St Helens, Merseyside  
United Kingdom  
T + 44 (0) 1744 88 7600 - F + 44 (0) 1744 88 9916

**Distributor**

Alkegen (formerly Unifrax)  
Kleinreinsdorf 62  
DE- 07989 Teichwolframsdorf  
Germany  
T + 49 (0) 366 24 40020 - F + 49 (0) 366 24 40099

**Distributor**

Alkegen (formerly Unifrax)  
Shaftsbury Street  
DE23 8XA Derby  
United Kingdom  
T +44 (0) 1332 331808

**Distributor**

Alkegen (formerly Unifrax)  
Via Volonterio 19  
21047 Saronno (VA)  
Italy  
T +39 02 967 01 808 - F +39 02 962 5721

**Email competent person**

reachsds@alkegen.com

**Distributor**

Alkegen (formerly Unifrax)  
17 Rue Antoine Durafour  
42420 Lorette  
France  
T +33 (0) 477 737 032 - F +33 (0) 477 733 991

**Distributor**

Alkegen (formerly Unifrax)  
Ruská 311, Pozorka  
CZ- 417 03 Dubí 3  
Czech Republic  
T + 42 (0) 417 800 356 - F + 42 (0) 417 539 838

**Distributor**

Alkegen (formerly Unifrax)  
Cristobal Bordiu 20  
ES- 28003 Madrid  
Spain  
T + 34 91 395 2279 - F + 34 91 395 2124

**1.4. Emergency telephone number**

Emergency number : Occupational Hygiene and CARE: Tel: + 44 (0) 1744 887603; Email: reachsds@alkegen.com; (8.15-17.10 h); Language : English

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin sensitisation, Category 1 H317  
Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

May cause an allergic skin reaction.

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

Precautionary statements (CLP)

: P261 - Avoid breathing mist, vapours, spray.

P280 - Wear protective gloves, protective clothing, eye protection.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

### 2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methylpropan-1-ol (78-83-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
methanol (67-56-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methyl-2H-isothiazol-3-one (2682-20-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	≥ 1 – < 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
titanium dioxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 13463-67-7 EC-No.: 236-675-5	≥ 1 – < 2.5	Not classified
2-methylpropan-1-ol substance with national workplace exposure limit(s) (GB)	CAS-No.: 78-83-1 EC-No.: 201-148-0 EC Index-No.: 603-108-00-1	≥ 0.25 – < 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
ethylbenzene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	≥ 0.25 – < 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 (ATE=17.8 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
methanol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	≥ 0.1 – < 0.25	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation:vapour), H331 (ATE=3 mg/l/4h) STOT SE 1, H370
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	< 0.1	Acute Tox. 2 (Inhalation), H330 (ATE=0.1 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=242 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=120 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 EUH071
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=670 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	( 3 ≤C < 10) STOT SE 2, H371 ( 10 ≤C < 100) STOT SE 1, H370
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	( 0.0015 ≤C ≤ 100) Skin Sens. 1A, H317
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	( 0.05 ≤C < 100) Skin Sens. 1, H317

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	----------------------------------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.
--------------------------------------------------	-----------------------------------------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Concerning personal protective equipment to use, see section 8.  
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapours, spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.  
Other information : Disposal must be done according to official regulations.

#### 6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing mist.  
Hygiene measures : Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.  
Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>titanium dioxide (13463-67-7)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>2-methylpropan-1-ol (78-83-1)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	2-Methylpropan-1-ol
WEL TWA (OEL TWA) [1]	154 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	231 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	75 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>ethylbenzene (100-41-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethylbenzene
IOEL TWA	442 mg/m <sup>3</sup>
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m <sup>3</sup>
IOEL STEL [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m <sup>3</sup>

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	552 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### methanol (67-56-1)

#### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Methanol
IOEL TWA	260 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

#### United Kingdom - Occupational Exposure Limits

Local name	Methanol
WEL TWA (OEL TWA) [1]	266 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

<b>xylene (1330-20-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	442 mg/m <sup>3</sup>
Acute - local effects, inhalation	442 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>
Long-term - systemic effects, oral	12.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65.3 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m <sup>3</sup>

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2.31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6.58 mg/l
<b>2-methylpropan-1-ol (78-83-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - local effects, inhalation	310 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - local effects, inhalation	55 mg/m <sup>3</sup>
<b>methanol (67-56-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	20 mg/kg bodyweight/day
Acute - systemic effects, inhalation	130 mg/m <sup>3</sup>
Acute - local effects, inhalation	130 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	20 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	130 mg/m <sup>3</sup>
Long-term - local effects, inhalation	130 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	4 mg/kg bodyweight
Acute - systemic effects, inhalation	26 mg/m <sup>3</sup>
Acute - systemic effects, oral	4 mg/kg bodyweight
Acute - local effects, inhalation	26 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	26 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4 mg/kg bodyweight/day
Long-term - local effects, inhalation	26 mg/m <sup>3</sup>
<b>tin dioxide (18282-10-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	5.7 mg/kg bodyweight/day
Acute - systemic effects, inhalation	2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	5.7 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2 mg/m <sup>3</sup>

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	2 mg/kg bodyweight
Acute - systemic effects, inhalation	6 mg/m <sup>3</sup>
Acute - systemic effects, oral	2 mg/kg bodyweight
Long-term - systemic effects, oral	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	2 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (marine water)	0.01 mg/l
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>2-methyl-2H-isothiazol-3-one (2682-20-4)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	0.043 mg/m <sup>3</sup>
Long-term - local effects, inhalation	0.021 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, oral	0.053 mg/kg bodyweight/day
Acute - local effects, inhalation	0.043 mg/m <sup>3</sup>
Long-term - systemic effects, oral	0.027 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.021 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	3.39 µg/L
PNEC aqua (marine water)	3.39 µg/L
PNEC aqua (intermittent, freshwater)	3.39 µg/L
PNEC aqua (intermittent, marine water)	3.39 µg/L
<b>PNEC (Soil)</b>	
PNEC soil	0.047 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	0.23 mg/l
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6.81 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, inhalation	1.2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.345 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	4.03 µg/L
PNEC aqua (marine water)	0.403 µg/L

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PNEC aqua (intermittent, freshwater)	1.1 µg/L
PNEC aqua (intermittent, marine water)	0.11 µg/L
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	49.9 µg/kg dw
PNEC sediment (marine water)	4.99 µg/kg dw
<b>PNEC (Soil)</b>	
PNEC soil	3 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	1.03 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses with side shields

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Chemically resistant protective gloves. Nitrile rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Liquid product : Inhalation unlikely. If dust are formed : Wear appropriate mask, Particle filter, P2. EN 149

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Grey.
Appearance	: Suspension.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: Not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

FyreWrap® LiB G2 Coating	
ATE CLP (oral)	> 5000 mg/kg bodyweight
ATE CLP (dermal)	> 5000 mg/kg bodyweight

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ATE CLP (dust,mist)	> 10 mg/l/4h
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)
Not rapidly degradable	

<b>xylene (1330-20-7)</b>	
LC50 - Fish [1]	2.6 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))
EC50 - Crustacea [1]	2.2 mg/l (24 h; Daphnia magna; (OECD 202 method))
ErC50 algae	2.2 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))
NOEC chronic fish	> 1.3 mg/l (56 d; Oncorhynchus mykiss)
NOEC chronic crustacea	0.96 mg/l (7 d; Ceriodaphnia dubia; US EPA 600/4-91-003)
<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l (96h; Menidia menidia)
LC50 - Fish [2]	4.2 mg/l (96; Oncorhynchus mykiss (Rainbow trout); (OECD 203 method))
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (48h; Daphnia magna)
EC50 72h algae	4.9 mg/l (72h; Skeletonema costatum)
EC50 72h - Algae [2]	5.2 mg/l (72h; Pseudokirchnerella subcapitata)
ErC50 algae	4.9 mg/l (72h; Skeletonema costatum)
NOEC chronic crustacea	0.96 mg/l (7d; Ceriodaphnia dubia)
<b>2-methyl-2H-isothiazol-3-one (2682-20-4)</b>	
LC50 - Fish [1]	4.77 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))
EC50 - Crustacea [1]	0.934 mg/l (48 h; Daphnia magna; (OECD 202 method))
EC50 72h algae	0.103 mg/l (72 h, Pseudokirchneriella Subcapita; (OECD 201 method))
ErC50 algae	0.072 mg/l (OECD 201 method)
NOEC chronic fish	4.93 mg/l (98 d; Oncorhynchus mykiss; (OECD 210 method))
NOEC chronic crustacea	0.044 mg/l (21 d; Daphnia magna; (OECD 211 method))
NOEC chronic algae	0.05 mg/l (5 d; Pseudokirchneriella subcapitata; (OECD 201 method))

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
LC50 - Fish [1]	2.18 mg/l (96 h; Onchorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	2.94 mg/l (48 h; Daphnia magna; OECD 202)
ErC50 algae	0.15 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)
NOEC chronic algae	0.055 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)

### 12.2. Persistence and degradability

<b>xylene (1330-20-7)</b>	
Persistence and degradability	Readily biodegradable.
<b>titanium dioxide (13463-67-7)</b>	
Persistence and degradability	Not applicable for inorganic substances.
<b>2-methylpropan-1-ol (78-83-1)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	70 – 80 % (28 d; (OECD 301D method))
<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	70 – 80 % (28d; ISO 14593-CO2-Headspace Test)
<b>methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	95 % (20 d)
<b>2-methyl-2H-isothiazol-3-one (2682-20-4)</b>	
Persistence and degradability	Not readily biodegradable. (OECD 301B method). (OECD 301D method).
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	85 % (63 d; (OECD 301C method))

### 12.3. Bioaccumulative potential

<b>2-methyl-2H-isothiazol-3-one (2682-20-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.486 (25 °C; (OECD 107 method))
Bioaccumulative potential	Bioaccumulation unlikely.
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
BCF - Fish [1]	6.95 (OECD 305 method)
Partition coefficient n-octanol/water (Log Kow)	0.7 (20 °C; pH 7; Test method EU A.8)

### 12.4. Mobility in soil

<b>2-methylpropan-1-ol (78-83-1)</b>	
Surface tension	69.7 mN/m (20 °C; 1 g/L; (OECD 115 method))
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.47 (calculated value)
<b>2-methyl-2H-isothiazol-3-one (2682-20-4)</b>	
Surface tension	68.8 mN/m (19 °C, EEC Method A5)

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ecology - soil	Low mobility (soil).
----------------	----------------------

### 12.5. Results of PBT and vPvB assessment

#### FyreWrap® LiB G2 Coating

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods

: Disposal must be done according to official regulations. European waste catalogue. Do not dispose of with domestic waste. Do not discharge into drains or the environment.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Take note of Directive 94/33/EC on the protection of young people at work.

#### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	xylene ; methanol ; 2-methylpropan-1-ol ; ethylbenzene
3(b)	FyreWrap® LiB G2 Coating ; xylene ; methanol ; 2-methylpropan-1-ol ; ethylbenzene
3(c)	xylene ; ethylbenzene
40.	xylene ; methanol ; 2-methylpropan-1-ol ; ethylbenzene
69.	methanol

#### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

#### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : MSDS of the supplier. ECHA (European Chemicals Agency).

Other information : Occupational Hygiene: dawn.webster@alkegen.com.

<b>Full text of H- and EUH-statements:</b>	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

# FyreWrap® LiB G2 Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:</b>		
----------------------------------------------------------------------------------------------------------------------------------	--	--

Skin Sens. 1	H317	Calculation method
--------------	------	--------------------

KFT SDS EU 06

The information presented on this SDS (1) provides details on material identity, manufacturer/supplier information, hazard characterization and prevention, emergency response and other specialized information, (2) is considered to be accurate to the best of our knowledge, information and good faith belief as of the date of publication, (3) is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release of the material named, (4) should be read and used in conjunction with the company's relevant literature, (5) relates only to the specific material designated and may not be valid for such material used in combination with any other material or process and (6) is provided without warranty, expressed or implied, in law or in fact, of merchantability or fitness for a particular purpose. This document does not constitute a product specification and should not be relied on as such. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product.