# **Specification Data Sheet**



# CMP-4200

Hydro-Fused<sup>®</sup>/Compressed MicroPore<sup>®</sup> Gasket Material F729190E33M9

## DESCRIPTION

CMP-4200 is a solvent-free, high performance compressed MicroPore gasket material. It was developed for steam, water, oil, and chemical resistance in Original Equipment and Industrial applications. It has exceptional sealability, torque retention, crush and blowout resistance, and is intended for applications with short duration maximum temperatures up to 350°C (650°F).

### **SPECIFICATION PROPERTIES**

Property	Value	Method
Density, g/cc(lb/cu.ft)	1.55 (97) (min.)	ASTM F 1315
Compressibility, % (at 34.5MPa)	7 - 17	ASTM F 36
Recovery, %	50 (min.)	ASTM F 36
Tensile Strength, AMD, MPa(psi)	12 (1740) (min.)	ASTM F 152
Flexibility, Mandrel Bend, 12 X Ga.	No Cracks	ASTM F 147
Fluid Resistance, IRM903 Oil		ASTM F 146
Change in Thickness, %	15 (max.)	
Change in Weight, %	25 (max.)	
Change in Tensile Strength, %	30 (max.)	
Change in Compressibility, %	17 (max.)	ASTM F 146
Fluid Resistance, Fuel B		
Change in Thickness, %	15 (max.)	
Change in Weight, %	20 (max.)	
Binder Type	Fully Cured Nitrile Butadiene/ Styrene Butadiene Rubber Blend	
Color	Grey	

#### **REMARKS AND RELATED DOCUMENTS**

Specification values determined by the test methods required for ASTM F-104, Type 7 materials.

EnCore<sup>®</sup>, Hydro-Fused<sup>®</sup>, MicroPore<sup>®</sup>, Pro-Formance<sup>®</sup>, Select-a-Seal<sup>®</sup>, Syntheseal<sup>®</sup>, Thermo-Tork<sup>®</sup>, and Voltoid<sup>®</sup> are registered trademarks of Interface Solutions, Inc. Select-a-Shield is a trademark of Interface Solutions, Inc.

WARNING: The description and performance data provided herein constitute a material specification for quality control purposes, but do not imply suitability for use in a specific application. Your specific application should not be undertaken without independent study and evaluation for suitability. Failure to select proper sealing products may result in either property damage or personal injury. For specific application recommendations, contact Interface Solutions. INTERFACE SOLUTIONS EXPRESSLY DISCLAIMS ALL WARRANTIES EITHER EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL ISI BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR PUNTIVE DAMAGES, HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THE INFORMATION CONTAINED IN ITS SPECIFICATION DATA SHEETS, ITS PRODUCTS OR THEIR FUTURE USE BY YOU OR ANY THIRD PARTIES, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Alkegen

Headquarters 5215 N. O'Connor Blvd, Suite 2300 Irving, TX 75039 Telephone: 716-768-6500 Website: www.alkegen.com Email: info@alkegen.com

**ALKEGEN** 

Form A-5767 Effective 02/25 © 2025 Alkegen All Rights Reserved