Product Information Sheet



N-8092

Syntheseal®/Nonasbestos Gasket Material F729900E59M9

DESCRIPTION

N-8092 is used in automotive, small engine, and compressor applications. It has excellent crush resistance at high flange pressures, and excellent sealing properties with oil, fuel, and water. It is intended for applications with short duration maximum temperatures up to 180°C (350°F).

SPECIFICATION PROPERTIES

| Property | Value | Method |
|---------------------------------|---------------------|-------------|
| Density, g/cc(lb/cu.ft) | 1.20 (75) (min.) | ASTM F 1315 |
| Compressibility, % (at 34.5MPa) | 15 - 30 | ASTM F 36 |
| Recovery, % | 35 (min.) | ASTM F 36 |
| Tensile Strength, AMD, MPa(psi) | 11.03 (1600) (min.) | ASTM F 152 |
| Fluid Resistance, IRM903 Oil | | ASTM F 146 |
| Change in Tensile Strength, % | 30 (max.) | |
| Change in Thickness, % | 20 (max.) | |
| Change in Compressibility, % | 40 (max.) | |
| Fluid Resistance, Fuel B | | ASTM F 146 |
| Change in Thickness, % | 20 (max.) | |
| Change in Weight, % | 30 (max.) | |
| Binder Type | Nitrile Butadiene | |

REMARKS AND RELATED DOCUMENTS

Specification values determined by the test methods required for ASTM F-104, Type 7 materials.

EnCore®, Hydro-Fused®, MicroPore®, Pro-Formance®, Select-a-Seal®, Syntheseal®, Thermo-Tork®, and Voltoid® are registered trademarks of Interface Solutions, Inc. Select-a-Shield is a trademark of Interface Solutions, Inc.

WARNING: The description and performance data provided herein constitute a material specification for quality control purposes, but do not imply suitability for use in a specific application. Your specific application should not be undertaken without independent study and evaluation for suitability. Failure to select proper sealing products may result in either property damage or personal injury. For specific application recommendations, contact Interface Solutions. INTERFACE SOLUTIONS EXPRESSLY DISCLAIMS ALL WARRANTIES EITHER EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL ISI BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIEBNICE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THE INFORMATION CONTAINED IN ITS SPECIFICATION DATA SHEETS, ITS PRODUCTS OR THEIR FUTURE USE BY YOU OR ANY THIRD PARTIES, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Form A-5780 Effective 09/25 © 2025 Alkegen All Rights Reserved Alkegen

Headquarters

5215 N. O'Connor Blvd, Suite 2300 Irving, TX 75039 Telephone: 716-768-6500 Website: www.alkegen.com Email: info@alkegen.com

